

UNCLASSIFIED

AD 401 572

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

401 572

(5) 17511

u

h1h83
S/198/62/008/005/002/009
D234/D308

COPY

STEP

AUTHOR: (5) Kayuk, Ya. P. (Kiev)

TITLE: (6) Postcritical state and stress concentration in flexible doubly connected plates

PERIODICAL: (15) Akademiya nauk Ukrayins'koyi RSR. Instytut mekhaniky. Prykladna mekhanika, v. 8, 5, 1962, 500-507

TEXT: The author attempts to formulate the problem of postcritical elastic state for a plate with free inner boundary and fixed outer boundary. The differential equations of the problem are quoted and the boundary conditions formulated. The boundary loads are represented as sums of critical forces and additional postcritical loads. The stress function and the forces are accordingly represented as sums of three terms, the first two corresponding to the terms of boundary loads, the third being a correction term. Dimensionless stresses are introduced. The differential equations are solved by expansion in terms of a small parameter $\eta = \varepsilon/(1 + \varepsilon)$, ε being the smaller of the postcritical terms of normal and tangential boundary load, divided by the critical term of the normal boundary load. Differential equations and boundary conditions are given for the terms in η , η^2 and η^3 . In the zero order approximation the deflection w_0 is equal to the eigenfunction corresponding to the minimal eigenvalue of the problem and multiplied by an arbitrary constant A. The solution of the first approximation w_1 exists only for determined values of A. The author deduces a nonlinear equation which A must satisfy in order that w_1 may exist. The geometrical nonlinearity of the problem is defined as the difference between the stressed state of the inner boundary of the plate and that of the fictitious inner boundary of a simply connected plate. Taking this into account, the author analyzes the variation of the stress concentration factor, with a numerical example. There are 2 figures.

Card 1/3

gential boundary load, divided by the critical term of the normal boundary load. Differential equations and boundary conditions are given for the terms in η , η^2 and η^3 . In the zero order approximation the deflection w_0 is equal to the eigenfunction corresponding to the minimal eigenvalue of the problem and multiplied by an arbitrary constant A. The solution of the first approximation w_1 exists only for determined values of A. The author deduces a nonlinear equation which A must satisfy in order that w_1 may exist. The geometrical nonlinearity of the problem is defined as the difference between the stressed state of the inner boundary of the plate and that of the fictitious inner boundary of a simply connected plate. Taking this into account, the author analyzes the variation of the stress concentration factor, with a numerical example. There are 2 figures.

Card 2/3

ASSOCIATION: Instytut mekhaniky AN URSR (Institute of Mechanics, AS UkrSSR)

SUBMITTED: June 11, 1962